MATERIAL SAFETY DATA SHEET



FLOYD READY ASSOC., INC.

96 Shubuta St. Jackson, MS 39209-2549 ph. 601-922-5367 or 800-647-7178 fx. 601-922-4458 or 877-922-4458 www.ferscosaws.com

SECTION 1

Product and Company Information

Product identifier Ready Slick

k

Product use Metalworking

lubricant

Manufacturer

ITW Fluids North America

3650 West Lake Avenue

Block

Glenview, Illinois 60026

1-800-452-5823

Emergency info

After 5:00pm CST: CHEMTREC, 1-800-424-9300

SECTION 2

Hazards Identification

Emergency overview

No hazards resulting from the material supplied.

HMIS rating

Health 0

Flammability 1 Reactivity 0 Personal B

protection Routes of entry

Skin, eyes, respiratory tract, digestive system.

Potential short-term

health effects

Skin

May cause mild irritation.

Eyes

May cause mild irritation.

Inhalation

May cause headache, dizziness and irritate the mucous membranes.

No hazards anticipated from ingestion incidental to industrial exposure.

Ingestion

Potential long-term None identified

health effects

SECTION 3

Chemical Composition/Hazardous Ingredients

Ingredients

CAS#

OSHA/PEL (TWA)

ACGIH/TLV (TWA)

Not applicable

N/AP

N/AP

N/AP

This product contains no chemicals subject to the reporting requirements of OSHA's Hazard Communication Standard 29 CFR 1910.1200.

Ready Slick

1 of 4

04/23/2013

SECTION 4 First Aid Measures

Skin contact Immediately wash the exposed area thoroughly with soap and water. Remove

contaminated clothing. Wash before reuse. If irritation persists, consult

physician.

In case of contact, immediately flush with water for at least 15 minutes. If Eye contact

irritation persists, consult physician.

Inhalation If inhaled, move to fresh air. If irritation persists, consult physician.

Ingestion If swallowed, DO NOT induce vomiting. Contact a physician immediately. If

vomiting occurs, keep head below hips to prevent aspiration of liquid into the

SECTION 5 Fire Fighting Measures

Flammability Non-flammable

Products of combustion Oxides of carbon (CO, CO₂).

Flash point (method) > 200°F (93°C) (PMCC)

Explosion data

Sensitivity to mechanical impact None

Sensitivity to static discharge None

Fire-fighting media In case of fire, use carbon dioxide, dry chemicals, foam, fog, sand, or earth.

and instructions

Special fire-fighting Self contained breathing apparatus and protective clothing is recommended to procedures/equipment protect fire fighters from any hazardous combustion or decomposition products.

Pressure build-up in the closed container may occur due to heat exposure.

Keep away from heat, sparks, flame or ignition sources.

SECTION 6 Accidental Release Measures

Personal precautions Use appropriate safety equipment. Avoid inhaling vapors or mist. Avoid contact

with eyes, skin and clothing.

Environmental precautions Do not allow spilled product to enter drains, sewers, or waterways.

Cleanup Ventilate area. Eliminate all sources of heat and flame. Stop leak if safe to do

so. Contain spill. Use absorbent material, such as vermiculite or sand. Place in

suitable container for later disposal.

Prohibited materials None

SECTION 7 Handling and Storage

Handling Use appropriate safety equipment. Use with adequate ventilation. Avoid

contact with eyes, skin and clothing. Keep away from extreme heat. Keep

container closed when not in use.

Store away from oxidizing agents, extreme heat, flame, or ignition sources. Storage

Store and use in a well ventilated area. Store in closed containers between

32°F and 75°F (0°C and 24°C).

SECTION 8

Exposure Controls and Personal Protection

Hygiene measures

Avoid contact with eyes, skin and clothing. Do not eat, drink, or smoke while

handling this product.

Control measures

General ventilation should be sufficient. Providing approved respirators for

emergencies, or when mist/vapor concentrations are unknown may be

warranted. Availability of eye wash station, washing facilities and safety shower

is recommended.

Personal protection

Skin

Wear suitable glove. Chemical resistant gloves, such as polyvinyl chloridecoated, are recommended. Wear protective clothing suitable to prevent contact. Remove contaminated clothing and launder before wearing.

Eyes

Safety glasses are recommended.

Respiratory

Not normally required. Control vapor or mist concentrations below exposure.

limits through use of general or local exhaust ventilation.



SECTION 9

Physical and Chemical Properties

Physical state

Solid

Color Blue **Odor Mild**

pH Not

applicable

Boiling point

> 400°F (204°C)

Melting/freezing point 110-120°F

(43-49°C)

Vapor pressure

< 1 mmHg

Solubility in water

Insoluble

Specific gravity

0.86

Vapor density >

1

Volatile organic compounds

Nil

SECTION 10

Reactivity and Stability

Stability and reactivity

Stable. Hazardous polymerization will not occur.

Conditions to avoid Extreme

heat

Materials to avoid Strong

oxidizers

Hazardous decomposition Thermal decomposition or burning will produce carbon monoxide, carbon

products

Ready Slick

dioxide, and thick smoke.

SECTION 11 Toxicological Information

LD50 Not determined for the product

LC50 Not determined for the product

Carcinogenic None of the ingredients in this product are listed by IARC, ACGIH, NTP or

OSHA as carcinogenic.

Teratogenicity No

information

Mutagenicity No

information

SECTION 12

Ecological Information

Environmental toxicity None

reported

Aquatic toxicity No

data

SECTION 13

Disposal Considerations

Handling for disposal

Absorb on suitable material and follow procedures listed below.

Methods of disposal

Dispose of in a manner that is recommended by local, state, provincial and

federal laws and regulations.

SECTION 14

Transportation Information

Not classified as hazardous for transport (DOT, TDG, CFR, IMO, ICAO).

SECTION 15 F

Regulatory Information

OSHA status

This product is not hazardous under the criteria of the Federal OSHA

Hazardous Communication Standard 29 CFR 1910.1200.

WHMIS information None

TSCA information

All ingredients are included in the TSCA inventory.

SARA Title III

Contains no ingredients which exceed De Minimus reporting requirements.

California Prop 65

The product contains no chemicals known to the state of California to cause

cancer or reproductive toxicity.

SECTION 16

Other Information

Prepared by

ITW Fluids North America, Leroy Hitchcock, 1-800-452-5823

Date of issue

April 23, 2013

Date of previous issue

March 21, 2011

References

- 1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices, 2004.
- 2. Canadian Centre for Occupational Health and Safety. CCInfoWeb databases, 2004.
- 3. US EPA Title III Lists of Lists October 2001 version.
- 4. Material Safety Data Sheets from manufacturer.

4 of 4

04/23/2013

Ready Slick